

IN THE CLAIMS:

The claims are as follows:

1. (Currently Amended) A frequency setting unit for a radio telecommunications network wherein base stations transmit at an accurately set frequency derived from a reference signal, the frequency setting unit comprising:
a radio receiver for receiving signals ~~at a first frequency~~ from a first base station transmitting signals at a first frequency and located in a first radio telecommunication network;
an analysis apparatus for analysing the received signals to determine the first frequency; and
a frequency setting apparatus responsive to the analysis apparatus and coupled to a second base station transmitting at a second frequency, and located in a second radio telecommunication network, for adjusting the second frequency with the aim of establishing a desired relationship between the second frequency and the first frequency.
2. (Previously Presented) A frequency setting unit as claimed in claim 1, wherein said reference signal is provided to the first base station by a reference clock where a pulse train is sent to a first controller controlling the first base station.
3. (Previously Presented) A frequency setting unit as claimed in claim 2, wherein said sent pulse train is used by the first controller to derive a set of pulse trains that are sent to said first base station.
4. (Previously Presented) A frequency setting unit as claimed in claim 1, wherein the second base station comprises a clock and the frequency setting unit is capable of transmitting a clock setting signal to the second base station for setting the clock.

5. (Original) A frequency setting unit as claimed in claim 4, wherein the clock setting signal comprises a stream of clock pulses.
6. (Currently Amended) A frequency setting unit according to claim 4 , wherein said clock setting signal transmitted to the second base station for setting said clock is derived from an internal clock within ~~said~~ a second controller controlling the second base station.
7. (Currently Amended) A frequency setting unit according to claim 4, wherein said clock setting signal to the second base station for setting said clock is derived straight from the detected frequency of said analysis apparatus.
8. (Previously Presented) A frequency setting unit according to claim 1, wherein said desired relationship is such that the second frequency matches the first frequency in an absolute manner.
9. (Currently Amended) A frequency setting unit according to claim 1, wherein said desired relationship is such that the second frequency is a multiple of the first frequency by shifting the frequency of said internal clock within a second controller controlling said second base station.
10. (Previously Presented) A frequency setting unit according to claim 1, wherein the said signals from the first base station (23) are broadcast signals.
11. (Cancelled)
12. (Cancelled)
13. (Previously Presented) A frequency setting unit as claimed in claim 1, wherein the frequency setting unit is comprised in said second controller controlling said second base station.

14. (Previously Presented) A frequency setting unit as claimed in claim 1, wherein the second base station is connected to the second telecommunications network by means of an asynchronous connection.
15. (Previously Presented) A frequency setting unit as claimed in claim 14, wherein the asynchronous connection is an internet protocol connection.
16. (Previously Presented) A frequency setting unit as claimed in claim 1, wherein at least one of said first and second telecommunications networks is operable according to a global system for mobile communications standard.
17. (Currently Amended) A method for frequency setting in a wireless telecommunications network such that base stations transmit at an accurately set frequency derived from a reference signal, wherein a first base station ~~transmitting~~transmits signals at a first frequency~~[[,]]~~ and a second base station ~~transmitting~~transmits signals at a second frequency~~[[,]]~~ and the first and second base stations are of different radio telecommunications networks; the method comprising the steps of:
- receiving signals in a radio receiver from the first base station;
 - analysing the received signals in an analysis apparatus to determine the first frequency; and
 - adjusting the second frequency in a frequency setting unit responsive to the analysis and coupled to the second base station with the aim of establishing a desired relationship between the second frequency and the first frequency.
18. (Previously Presented) A frequency setting unit as claimed in claim 1, wherein the frequency setting unit is a Base Station Controller.
19. (Previously Presented) A frequency setting control unit as claimed in claim 1, wherein the frequency control unit is provided on an expansion card.

20. (Currently Amended) An expansion card for a radio telecommunications network wherein base stations transmit at an accurately set frequency derived from a reference signal, the expansion card comprising:

a receiver for receiving signals from a first base station transmitting signals at a first frequency and located in a first radio telecommunications network;
an analysis apparatus for analysing the received signals to determine a first frequency; and
a frequency setting unit responsive to the analysis apparatus and coupled to a second base station~~[[;]]~~ transmitting signals at a second frequency and located in a second radio telecommunications network, for adjusting ~~at~~ the second frequency with the aim of establishing a desired relationship between the second frequency and the first frequency.

21. (Currently Amended) An expansion card as claimed in claim 20, wherein the expansion card is adapted to be inserted to a network element responsible ~~offor~~ controlling base station operations.

22. (Currently Amended) A frequency setting unit for a radio telecommunications network wherein base stations transmit at an accurately set frequency derived from a reference signal, the frequency setting unit comprising:

means for receiving signals ~~having a first frequency~~ from a first base station transmitting signals at a first frequency and located in a first radio telecommunications network;
means for analysing the received signals to determine the first frequency; and
means for adjusting a second frequency with the aim of establishing a desired relationship between the second frequency and the first frequency, the means for adjusting being responsive to the means for analysis and coupled to a second base station transmitting signals with the second frequency; and located in a second radio telecommunications network.

23. (Currently Amended) A base station for a radio telecommunications network, the base station comprising:

a radio receiver for receiving signals ~~having a first frequency~~ from a reference base station transmitting signals at a first frequency and located in a different radio telecommunication network from the base station;
an analysis apparatus for analysing the received signals to determine the first frequency;
a frequency setting unit responsive to the analysis apparatus for adjusting a second frequency with the aim of establishing a desired relationship between the second frequency and the first frequency and for sending a clock-setting signal ~~for~~ to a clock; and
~~the~~ clock for providing a clock signal for the base station, the clock being set according to the clock-setting signal from the frequency setting unit.

24. (Currently Amended) A network element for controlling base stations in a radio telecommunications network wherein base stations transmit at an accurately set frequency derived from a reference signal, the network element comprising:
a radio receiver for receiving signals ~~having a first frequency~~ from a first reference base station transmitting signals at a first frequency and located in a first radio telecommunications network;
an analysis apparatus for analysing the received signals to determine the first frequency; and
a frequency setting unit responsive to the analysis apparatus and coupled to a second base station transmitting signals at a second frequency~~[[;]]~~ and located in a second radio telecommunications network, for adjusting the second frequency with the aim of establishing a desired relationship between the second frequency and the first frequency.
25. (Previously Presented) A network element according to claim 24 wherein the network element is part of the second telecommunications network.
26. (Previously Presented) A network element according to claim 24 wherein the network element is a Base Station Controller.

27. (Currently Amended) A synchronization unit for a radio telecommunications network wherein base stations transmit at an accurately set frequency derived from a reference signal, the synchronization unit comprising:

a radio receiver for receiving signals ~~having a first frequency~~ from a first reference base station transmitting signals at a first frequency and located in a first radio telecommunication network,
an analysis apparatus for analysing the received signals to determine the first frequency; and
a connection for coupling the synchronization unit to a frequency setting unit responsive ~~to the analysis~~ for adjusting the frequency at which a second base station~~[[,]]~~ located in a second radio telecommunications network transmits signals.

28. (Previously Presented) A synchronization unit according to claim 27, where the synchronization unit is a mobile handset.

29. (Cancelled)

30. (Currently Amended) A system of at least first and second radio telecommunications networks wherein each base station of the system transmits signals at an accurately set frequency derived from a reference signal, the system comprising:

a radio receiver for receiving signals ~~having a first frequency~~ from a first reference base station transmitting signals at a first frequency and located in a first radio telecommunications network;
an analysis apparatus for analysing the received signals to determine the first frequency; and
a frequency setting unit responsive to the analysis apparatus and coupled to a second base station transmitting signals at a second frequency~~[[,]]~~ and located in a second radio telecommunications network, for adjusting the

second frequency with the aim of establishing a desired relationship between the second frequency and the first frequency.